

AirPrime® HL7802 LPWA Module

World's smallest multi-mode LPWA module offering best-in-class power performance for global LTE-M, NB-IoT, 2G, and GNSS networks

The HL7802 module for Cat-M1/NB1 worldwide networks with 2G fallback is fully compliant with the 3GPP Release 13 standard and is Release 14 ready to support NB2 features in the future, providing a new low-cost, best-in-class power technology for low-bandwidth IoT applications with extended reach beyond traditional cellular.

Delivering up to 300Kbps download speed and 375Kbps upload speed, this module is ideal for simple static sensor applications, or real-time fixed or mobile applications such as asset tracking and monitoring, industrial equipment, consumer wearables, smart city, healthcare and agricultural monitoring devices.

Design now with LPWA modules in the CF3® form factor and scale to 3G or 4G networks in the future as the application evolves.

Benefits



Common Form Factor

Compact CF3® design to migrate between technologies and future-proof product platforms



Global

Worldwide coverage on a single module with industry and mobile network certifications to get you to market faster



Embedded SIM

Ready-to-Connect solutions streamline operations and add future flexibility (optional)*



FOTA Upgrades

FREE unlimited firmware over-the-air (FOTA) upgrades future-proof deployments and keep them secure



Cloud Connected

Securely collect data and remotely manage your IoT deployments with integrated AirVantage® cloud services*



Secure Boot

Prevent unauthorized code on the target to keep your connectivity secure



Ultra-Low Power Mode

Best-in-class power performance extending the life of battery operated devices by 5-10X



Location Services

Integrated GNSS receiver enables tracking and location-based services*



TCP/IP Stack

Embedded stack to easily communicate over the internet



Programmability

Basic and Extended AT Commands simplify development



Industrial-Grade

Tested for harsh environments and extreme temperatures

*Supported as a future firmware upgrade

Technical Specifications

4G LTE

Category

Cat-M1/NB1

Frequency Bands

B1, B2, B3, B4, B5, B8, B9, B10, B12, B13, B14, B17, B18, B19, B20, B25, B26, B27, B28, B65, B66

2G

GPRS

900, 1800

GSM

900, 1800

DATA SPEED

Peak Download Rate

300Kbps

Peak Upload Rate

375Kbps

EMBEDDED SOFTWARE

Firmware

Pre-certified firmware, Secure boot

Digital Audio*

Audio

INTERFACES

1 X 8-wire

UART

1

USB

2

ADC

8

GPIO

1

Tx ON Indicator

1

SIM interface 1.8V/3V

HARDWARE

LGA

CF3 Form Factor

15x18x2.4mm

Dimensions

Industrial Grade: -40°C / +85°C

Temperature Range

APPROVALS

Vodafone

Planned Carrier

FCC, GCF, IC, PTCRB

Regulatory

CLOUD SERVICES

Free Unlimited FOTA upgrades, Connectivity Management option, Device Management option

CONNECTIVITY

Optional Ready-to-Connect Sierra Wireless embedded SIM

* Supported as a future firmware upgrade