



Fuse-link, high speed, 315 A, AC 690 V, size 1, 53 x 69 x 51 mm, aR, IEC, UL, single indicator, flush end, M8



Catalog No. 170M4410

Delivery program

| | | | |
|------------------------------|---|----|-------------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 315 |
| Rated voltage | | | AC 690 V |
| Construction size | | | size 1 |
| Utilization category | | | aR |
| Status indicator | | | single (top) indicator system |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | IEC UL |
| Shape | | | square body with flush end contacts |
| Standards/Regulations | | | IEC 60269-4 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 315 |
| Rated voltage | | V | 690 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 200 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | Top fuse status indicator |
| Insulated metal gripping lugs (IMGL) | | | No |

Additional product information (links)

| | |
|--------------------------------------|---|
| High-speed full-line catalogue (pdf) | http://www1.cooperbusmann.com/pdf/dc416ece-4392-4b42-ab36-39df6058b353.pdf |
|--------------------------------------|---|