



Fuse-link, high speed, 315 A, AC 690 V, compact size 1, 43 x 59 x 141 mm, aR, DIN, IEC, visual indicator



Catalog No. 170M3906

Delivery program

| | | | |
|------------------------------|---|----|---|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 315 |
| Rated voltage | | | AC 690 V |
| Construction size | | | compact size 1 |
| Size | | | 43 x 59 x 141 mm |
| Utilization category | | | aR |
| Status indicator | | | visual indicator |
| Description | | | live gripping lugs |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | semiconductor protection |
| Standard/Approval | | | DIN IEC |
| Shape | | | square body with centre-bolted tags (slotted) |
| Standards/Regulations | | | IEC 60269-4 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 315 |
| Rated voltage | | V | 690 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 200 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | Top fuse status indicator |
| Insulated metal gripping lugs (IMGL) | | | No |

Additional product information (links)

| | |
|-------------------------|---|
| Product datasheet (pdf) | http://www1.cooperbussmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf |
|-------------------------|---|