



Fuse-link, high speed, 1250 A, DC 750 V, size 23, 92 x 148 x 161 mm, gR, IEC, single indicator

Catalog No. 170M2018

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1250
Rated voltage			DC 750 V
Construction size			size 23
Size			92 x 148 x 161 mm
Utilization category			gR
Status indicator			single indicator
Description			dual-barrel indicator style K for microswitch
Breaking Capacity		kA	110
usable for size/applications			traction third rail
Standard/Approval			IEC
Shape			square body with parallel bolted tags
Standards/Regulations			IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	1250
Rated voltage		V	750
Voltage type			DC
Voltage type			DC
Rated switching capacity		kA	110
Utilization category			gR (general purpose semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusssmann.com/pdf/2ef86aed-e370-419c-ad0a-89df8d9dab6c.pdf
-------------------------	---