



**Fuse-link, high speed, 700 A, AC 690 V, size 1, 53 x 69 x 136 mm, aR, IEC, UL, no indicator, 115 mm centers**

**Catalog No. 170M4717**

**Delivery program**

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	700
Rated voltage			AC 690 V
Construction size			size 1
Size			53 x 69 x 136 mm
Utilization category			aR
Description			US style
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			IEC UL
Shape			square body with centre-bolted tags
Standards/Regulations			IEC 60269-4

**Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	700
Rated voltage		V	690
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No