



Fuse-link, high speed, 63 A, AC 660 V, size 0000, 18 x 19 x 80 mm, aR, UL

Catalog No. 170M0215

Similar to illustration

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	63
Rated voltage			AC 660 V
Construction size			size 0000
Size			18 x 19 x 80 mm
Utilization category			aR
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			UL
Shape			square body with offset bolted tags
Standards/Regulations			UL 248-13

### Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	63
Rated voltage		V	660
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www1.cooperbusmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf">http://www1.cooperbusmann.com/pdf/4a317260-8e98-40d9-b43b-e80c53a102f6.pdf</a>
-------------------------	---