



Fuse-link, high speed, 350 A, AC 690 V, compact DIN 1, 45 x 59 x 104 mm, aR, DIN, IEC, single indicator

Catalog No. 170M3118

### Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	350
Rated voltage			AC 690 V
Construction size			compact DIN 1
Size			45 x 59 x 104 mm
Utilization category			aR
Status indicator			single indicator
Description			indicator style K for microswitch
Breaking Capacity		kA	200
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

### Technical data ETIM 7.0

Veiligheidsschakelaars en zekeringen (EG000020) / Smeltpatroon (mes) (EC000055)			
Elektro-, automatiserings- en procesbesturingstechniek / Electroinstallatie, -toestel / Smeltzekeringselement / NH-zekeringselement (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
DIN-grootte			Overig
Nom. (meet)stroom		Amp	350
Nom. (meet)spanning		Volt	690
Spanningstype			AC
Nom. afschakelvermogen		Kiloamp	200
Bedrijfsklasse			aR (deelbereik stroomomvormerbeveiliging)
Uitvoering kenmelder			Overig
Geïsoleerde metalen trekoren (IMGL)			Nee

### Additional product information (links)

Product datasheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720015_170M.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720015_170M.pdf</a>
-------------------------	---