

# DATASHEET - FUSE 315A 690V 1\*GN/50 AR UC



Fuse-link, high speed, 315 A, AC 690 V, compact size 1, 45 x 59 x 51 mm, aR, IEC, UL, single indicator



**Part no.** FUSE 315A 690V 1\*GN/50 AR UC  
**Catalog No.** 170M3517

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	315
Rated voltage			AC 690 V
Construction size			compact size 1
Size			45 x 45 x 140 mm
Utilization category			aR
Status indicator			single (top) indicator system
usable for size/applications			DC common bus, DC drives, power converters/rectifiers
Standard/Approval			UL IEC
Shape			square body with flush end contacts
Standards/Regulations			UL Recognized IEC Rated

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	315
Rated voltage		V	690
Voltage type			
Rated switching capacity		kA	
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Top fuse status indicator
Insulated metal gripping lugs (IMGL)			No