



Fuse-link, high speed, 400 A, AC 1000 V, compact DIN 1, 43 x 61 x 138 mm, aR, DIN, IEC, type K indicator



Catalog No. 170M3975

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	400
Rated voltage			AC 1000 V
Construction size			compact DIN 1
Size			43 x 61 x 138 mm
Utilization category			aR
Status indicator			single indicator
Description			indicator style K for microswitch
Breaking Capacity		kA	150
usable for size/applications			semiconductor protection
Standard/Approval			DIN IEC
Shape			square body with centre-bolted tags (slotted)
Standards/Regulations			DIN 43653 IEC 60269-4

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	400
Rated voltage		V	1000
Voltage type			AC
Rated switching capacity		kA	125
Utilization category			aR (accompanied semiconductor protection)
Type of fuse status indicator			Other
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720058_Square_Body_DIN_43_653.pdf
-------------------------	---