



828904-1 Product Details



828904-1

TE Internal Number: 828904-1



Timer Contacts

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Timer Products Product Line
- 1.5/2.5/4.0mm Pin Diameter Connector System Series, Junior-Power-Timer (JPT) Series, MCON Series, Multiple Contact Point (MCP) Series
- Wire-to-Wire
- Applies To Wire/Cable
- Accessory

Documentation & Additional Information

Product Drawings:

- Einzeldichtung (DIA 5.6) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- splash proof conn. w.s.lock for junior power timer c... (PDF, English)
- 15 Position J.P.T. Sealed Female Connector (PDF, English)
- 10 & 29 pos. door to body (PDF, English)
- 55 POS. J.P.T. WATER PROOF CONNECTOR (PDF, English)

Application Specifications:

- APPLICATION SPECIFICATION FOR JUNION POWER TIMER CON... (PDF, English)

Instruction Sheets:

- 2-Position, 1.5 mm, Socket Receptacle Connector Assembly (PDF, English)
- 10-Position Circular Through Wall Connector Assembl... (PDF, English)

CAD Files: (CAD Format & Compression Information)

- 2D Drawing (DXF, Version M)
- 3D Model (IGES, Version M)
- 3D Model (STEP, Version M)

Additional Information:

- [Product Line Information](#)

Additional Product Images:

- [Line Drawing](#)

Related Products:

- [Tooling](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Line = Timer Products
- Series = 1.5/2.5/4.0mm Pin Diameter Connector System, Junior-Power-Timer (JPT), MCON, Multiple Contact Point (MCP)
- Product Type = Accessory
- Accessory Type = Wire Seal
- Cable Type = FLR (Thin Walled Cable)
- Termination Method to Wire/Cable = Crimp

Body Features:

- Single Wire Sealing System = Yes

Configuration Features:

- GET 0.64 Connector System = Yes

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- Applies To = Wire/Cable
- Accepts Wire Insulation Diameter, Range (mm [in]) = 1.20 - 2.10 [0.047 - 0.082]

Operation/Application:

- Application Use = Wire-to-Wire

Packaging Features:

- Packaging Method = Loose Piece
- Packaging Quantity = 1,000

Other:

- Brand = AMP