

# ATP-ST 4 - Partition plate



3030721

<https://www.phoenixcontact.com/us/products/3030721>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

Partition plate, length: 59.8 mm, width: 2 mm, height: 39 mm, color: gray



## Commercial Data

Item number	3030721
Packing unit	1 pc
Minimum order quantity	50 pc
Sales Key	BE29
Product Key	BE2Z1X
Catalog Page	Page 104 (C-3-2013)
GTIN	4017918187965
Weight per Piece (including packing)	2.748 g
Weight per Piece (excluding packing)	2.78 g
Customs tariff number	39269097
Country of origin	DE

# ATP-ST 4 - Partition plate



3030721

<https://www.phoenixcontact.com/us/products/3030721>

## Technical Data

### Product properties

Product type	Partition plate
--------------	-----------------

### Dimensions

Width	2 mm
Height	39 mm
Height NS 35/15	48 mm
Height NS 35/7,5	40.5 mm
Length	59.8 mm

### Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

# ATP-ST 4 - Partition plate



3030721

<https://www.phoenixcontact.com/us/products/3030721>

## Classifications

### ECLASS

ECLASS-10.0.1	27141133
ECLASS-11.0	27141133
ECLASS-12.0	27141133
ECLASS-13.0	27250301

### ETIM

ETIM 8.0	EC000886
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# ATP-ST 4 - Partition plate

3030721

<https://www.phoenixcontact.com/us/products/3030721>



## Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	-----------------------------------------------------------------------------------------------------------

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)