

Click to view price, real time Inventory,  
Delivery & Lifecycle Information ;

# SSAG130400

ALPS Electric

Slide Switches 3Pos left-side recoil Flat w/lug

Any questions, please feel free to contact us.

[info@kaimte.com](mailto:info@kaimte.com)

Long life recoil type meeting more compact and low-profile needs



### Typical Specifications

Items		Specifications
Rating (max.)/(min.) (Resistive load)		10mA 5V DC / 50μA 3V DC
Contact resistance (Initial performance / After lifetime)		200mΩ max. / 500mΩ max.
Operating force		1N (Recoil side) 1.5N (Lock side)
Operating life	Without load	100,000 cycles (Recoil side) 30,000 cycles (Lock side)
	With load	100,000 cycles (Recoil side) 30,000 cycles (Lock side) (10mA 5V DC)


### Product Line

Travel (mm)	Operating section directions	Poles	Positions	Changeover timing	Soldering	Operating	Shape of flame leg	Location lug	Minimum order unit (pcs.)		Products No.	Drawing No.		
									Japan	Export				
1.5	Horizontal	1	3	Not specified	Reflow	Left-side recoil	For PC board insert	Without	4,000	16,000		SSAG130100	1	
								With				SSAG130200		
							Flat	Without				2	SSAG130300	
								With					SSAG130400	
							Right-side recoil	For PC board insert				Without	3	SSAG230100
												With		SSAG230200
						Flat	Without	4	SSAG230300					
							With		SSAG230400					
						Double-side recoil	For PC board insert	Without	5	SSAG330100				
								With		SSAG330200				
							Flat	Without	6	SSAG330300				
								With		SSAG330400				


### Packing Specifications

Taping

Number of packages (pcs.)			Tape width (mm)	Export package measurements (mm)
1 reel	1 case /Japan	1 case /export packing		
4,000	8,000	16,000	24	428×413×172









### Circuit Diagram (Viewed from Direction A)



Dimensions

Unit:mm

No.	Style	PC board mounting hole and land dimensions (Viewed from the direction A)
1	<p><b>With boss</b></p>  <p>Terminal No.①</p> <p>Travel:momentary A / B \ C Travel:with detent</p> <p>Operating force : B → C C → B 1.5N B → A 1N</p>	 <p>Note the arrangement of circuit patterns</p>
2	<p><b>With boss</b></p>  <p>Terminal No.①</p> <p>Travel:momentary A / B \ C Travel:with detent</p> <p>Operating force : B → C C → B 1.5N B → A 1N</p>	 <p>Note the arrangement of circuit patterns</p>
3	<p><b>With boss</b></p>  <p>Terminal No.①</p> <p>Travel:with detent A / B \ C Travel:momentary</p> <p>Operating force : B → A A → B 1.5N B → C 1N</p>	 <p>Note the arrangement of circuit patterns</p>

Dimensions

Unit:mm

No.	Style	PC board mounting hole and land dimensions (Viewed from the direction A)
4	<p><b>With boss</b></p> <p>Terminal No.①</p> <p>9.05 4-0.4 0.2 0.6 3 1.5 1.4 1.5 1.5 1.15 10.17 2-φ0.8 5 0.5</p> <p>Travel:with detent A / B \ C Travel:momentary</p> <p>Operating force : B→A A→B 1.5N B→C 1N</p>	<p>2-φ0.9 hole</p> <p>0.9 1.1 5 8.8 1.1 4-0.7 0.65 1.9 2.5</p> <p>Note the arrangement of circuit patterns</p>
5	<p><b>With boss</b></p> <p>Terminal No.①</p> <p>9.05 4-0.4 0.2 0.6 3 1.5 1.4 1.5 1.5 1.15 8.77 2-φ0.8 5 0.5</p> <p>Travel:momentary A / B \ C Travel:momentary</p> <p>Operating force : B→A B→C 1N</p>	<p>2-φ0.9 hole</p> <p>1.4 0.9 0.45 1.2 5 8 1.2 8.92 4-0.7 0.65 1.9 2.5</p> <p>Note the arrangement of circuit patterns</p>
6	<p><b>With boss</b></p> <p>Terminal No.①</p> <p>9.05 4-0.4 0.2 0.6 3 1.5 1.4 1.5 1.5 1.15 10.17 2-φ0.8 5 0.5</p> <p>Travel:momentary A / B \ C Travel:momentary</p> <p>Operating force : B→A B→C 1N</p>	<p>2-φ0.9 hole</p> <p>0.9 1.1 5 8.8 1.1 4-0.7 0.65 1.9 2.5</p> <p>Note the arrangement of circuit patterns</p>











Note

Dimensions drawing is for type with location lugs.

Detector  
Slide  
Push  
Rotary  
Power  
Dual-in-line  
Package Type  
Small size  
General Use Type  
Big size  
General Use Type

# Slide Switches

## List of Varieties


Series		SSAJ	SSSS8	SSAL	SSAG	SSSS7
Photo						
Actuator direction	Horizontal	●	●	●	●	●
	Vertical	—	●	—	—	—
Poles-positions	1-2	●	●	●	—	●
	1-3	—	●	—	●	●
	1-4	—	—	—	—	—
	2-2	—	●	—	—	—
	2-3	—	●	—	—	—
	2-4	—	—	—	—	—
	4-2	—	—	—	—	—
Travel (mm)		1.4	1.5, 2	2	1.5	2
Operating temperature range		-10°C to +60°C	-40°C to +85°C	-10°C to +60°C		-40°C to +85°C
Automotive use		—	—	—	—	—
Life cycle						
Rating (max.) (Resistive load)		10mA 5V DC	0.3A 5V DC	10mA 5V DC		0.3A 4V DC
Rating (min.) (Resistive load)		50μA 3V DC				
Durability	Operating life without load	10,000 cycles 500mΩ max.	10,000 cycles 100mΩ max.	100,000 cycles 10Ω max.	30,000 cycles (Lock side) 100,000 cycles (Recoil side) 500mΩ max.	10,000 cycles 100mΩ max.
	Operating life with load Load: as rating		10,000 cycles 130mΩ max.			10,000 cycles 130mΩ max.
Electrical performance	Initial contact resistance	300mΩ max.	70mΩ max.	10Ω max.	200mΩ max.	70mΩ max.
	Insulation resistance	100MΩ min. 100V DC				100MΩ min. 500V DC
	Voltage proof	100V AC for 1minute				500V AC for 1minute
Mechanical performance	Terminal strength	3N for 1minute				
	Actuator strength	Operating direction	10N			
Pulling direction						
Environmental performance	Cold	-40°C 96h	-40°C 500h	-40°C 96h		-20°C 500h
	Dry heat	85°C 96h	85°C 500h	85°C 96h		85°C 500h
	Damp heat	40°C, 90 to 95%RH 96h	60°C, 90 to 95%RH 500h	40°C, 90 to 95%RH 96h		60°C, 90 to 95%RH 500h
Page		72	74	77	79	82

Slide Switches Soldering Conditions	106
Slide Switches Cautions	107

**Note**  
 ● Indicates applicability to all products in the series.

## Example of Reflow Soldering Condition

1. Heating method: Double heating method with infrared heater.
2. Temperature measurement: Thermocouple  $\phi$  0.1 to 0.2 CA (K) or CC (T) at soldering portion (copper foil surface).  
A heat resisting tape should be used for fixed measurement.
3. Temperature profile



Series (Reflow type)		A (°C) 3s max.	B (°C)	C (s)	D (°C)	E (°C)	F (s)
SSSS2	Vertical 1-pole, 3-position	260	230	40	180	150	120
	Horizontal 1-pole, 2-position 1-pole, 3-position 2-pole, 3-position						
	Vertical 1-pole, 2-position	250					
SSAG, SSAJ, SSAL, SSSS8, SSS7		260					

### Notes

1. The condition mentioned above is the temperature on the mounting surface of a PC board. There are cases where the PC board's temperature greatly differs from that of the switch, depending on the PC board's material, size, thickness, etc. The above-stated conditions shall also apply to switch surface temperatures.
2. Soldering conditions differ depending on reflow soldering machines. Prior verification of soldering condition is highly recommended.

## Reference for Hand Soldering

Series	Soldering temperature	Soldering time
SSSF, SSSU	350±10°C	3+1/0s
SSSS2	350±10°C	4s max.
SSSS9	350±10°C	3s max.
SSAG, SSAJ, SSAL	350±5°C	3s max.
SSSS8	330±5°C	3s max.
SSSS7	320±5°C	3s max.
SSAC	300±10°C	2s max.

## Reference for Dip Soldering

(For PC board terminal types)

Series	Items		Dip soldering	
	Preheating temperature	Preheating time	Soldering temperature	Duration of immersion
SSSS2	100°C max.	60s max.	260±5°C	3±1s
SSSS9	120°C max.	60s max.	260±5°C	5+0/-1s (2 times)
SSSF, SSSU	100°C max.	60s max.	260±5°C	10±1s/5±1s
SSAC	100°C max.	60s max.	260±5°C	5±1s

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Alps Alpine:](#)

[SSAG130100](#) [SSAG130200](#) [SSAG130300](#) [SSAG130400](#) [SSAG230100](#) [SSAG230200](#) [SSAG230300](#)  
[SSAG230400](#) [SSAG330100](#) [SSAG330200](#) [SSAG330300](#) [SSAG330400](#)